




## Symbol



## Features

1. For high pressure use, corrosion and chemical resistance.
2. Good performance in chemically working environments and outdoor facility.
3. Suitable for semi-conductor industry.
4. Effectively removes water and particle.
5. Strict quality control.
6. Light weight, compact size for space saving.



## How to order

SSF200	—	02	N	C	H
Stainless Steel SUS316 Miniature		Port size	Thread	Filtration	Drain
Miniature Filter		02 : 1/4"	Blank : G N : NPT R : Rc	Blank : 5µm C : 40µm	Blank : Semi-auto drain H : Manual drain

## Specifications

Model	SSF200
Port size	1/4"
Fluid	Compressed air
Body material	Stainless steel SUS316
Bowl material	Stainless steel SUS316
Filter element material	Stainless steel SUS316
Filtration	5µm (Standard), 40µm (Option)
Operating pressure range	0 ~ 20 kgf/cm <sup>2</sup>
Proof pressure	30 kgf/cm <sup>2</sup>
Max. flow rate	1900 l/min
Ambient temperature	-10°C ~ 60°C
Filter bowl capacity	105cc
Standard drain	Semi-auto drain (Drains below 0.5kgf/cm <sup>2</sup> )
Net weight	1260g
Accessories	Mounting bracket, Plug

## Dimensions

