


Symbol



Features

1. Operating pressure range 0 ~ 20 kgf/cm².
2. Accurate and easy pressure setting.
3. Stainless steel pressure gauge filled oil as standard accessory for more stable pressure indication.

How to order

Regulator	Port size	Thread	Function option	Mounting bracket
UHR - 02	02 : 1/4"	N : G	V : Relief	B12 : W/I mounting bracket
	03 : 3/8"	N : NPT	V : No-Relief	B12 : W/I panel nut
	04 : 1/2"			B14 : W/I panel nut + L type bracket

*For non-relieving type, the secondary pressure is not allowed to be exhausted when it is higher than setting pressure.

Specifications

Model	UHR-02	UHR-03	UHR-04
Port size	1/4"	3/8"	1/2"
Fluid	Compressed air		
Regulator construction	Piston		
Body material	Aluminum die-cast		
Operating pressure range	0 ~ 20 kgf/cm ²		
Max. inlet pressure	20 kgf/cm ²		
Max. flow rate l/min (ANR) 40µm	2800		
Ambient temperature	-10℃ ~ 60℃		
Net weight	560g	550g	540g
Accessories	Pressure gauge(KUX0000046), Mounting bracket set, Plug		
Option	Panel nut, L type bracket		

Dimensions

UHR-02, 03, 04

