

Features

- 1. 3/2 way solenoid valve, direct acting for quick and sensitive response.
- 2. Large flow rate.
- 3. The valve is easy to be installed, which simplifies pipe connection.
- 4. Coil nut is available, please refer to page 5-3.

\*Stainless steel valve body can be customized.



How to order

AM325 – 02	N	–	S	2	L	E
3/2 Way	Port size	Thread	Solenoid	Voltage	Led	Coil type
	02 : 1/4"	Blank : G	S : Single solenoid	1 : 110VAC	Blank : W/O LED	Blank : DIN
	03 : 3/8"	N : NPT		2 : 220VAC	L : W/I LED	E : Ex-proof
		R : Rc		6 : 24VAC		
				7 : 12VDC		
				9 : 24VDC		


\*Ex-proof coil is available, please refer to page 5-9.

Specifications


Model	AM325-02-S	AM325-03-S
Port size	1/4"	3/8"
Body material	Aluminum alloy	
Fluid	Compressed air	
Effective area	3.8mm <sup>2</sup>	4.2mm <sup>2</sup>
Acting	Direct acting with spring return	
Operating pressure range	0 ~ 6 kgf/cm <sup>2</sup>	
Proof pressure	7 kgf/cm <sup>2</sup>	
Ambient temperature	-10℃ ~ 60℃	
Duty cycle	100% ED	
Coil type	DIN	
Protection class	IP65 (DIN 40 050)	
Insulation class	F	
Voltage tolerance	± 10%	
Standard voltage	220VAC, 110VAC, 24VDC (The other voltage is optional)	
Net weight	270g	370g

Dimensions

AM325-02



AM325-03



Flow chart

