

Features

1. To be installed in moving devices like air cylinder, slide, etc.
2. Various operating styles.
3. Panel bore size Ø30 (Option Ø25).



How to order

MSV8632	01	N	R	G
MSV8622 :Single	Port size	Thread	Operator	Operator color
MSV8642 :Stack	01 :1/8"	Blank :G	R :Roller	Blank :Standard color
MSV8632 :Single (with exhaust port)		N:NPT	RL :One way roller	G:Green
MSV8662 :Stack (with exhaust port)		R:Rc	TB :Twist selector	B:Black
			LB :Long twist selector	Y:Yellow
			PP :Palm button (Flush)	
			PPL :Palm button (Extended)	
			EB :Latching button	

*MSV8642 & MSV8662 for TB operator only(Black).

Operator color

Operator	Standard	Option		
TB/LB	Black	Red	---	---
PB/PP/PPL	Red	Black	Green	Yellow
EB	Red	---	---	---

Specifications

Model	MSV8632-01	MSV8642-01TB
Port size	1/8"	
Body material	Aluminum alloy	
Panel dimension	30mm (Option:25mm)	
Fluid	Compressed air	
Sectional area	1.8mm ²	
Operating pressure range	0 ~ 9 kgf/cm ²	
Max. operating pressure	10 kgf/cm ²	
Ambient temperature	-10°C ~ 60°C	
Standard operator color	Black: TB, LB; Red: PB, PP, PPL, EB	

Dimensions

MSV8622-01	MSV8632-01	MSV8642-01TB, MSV8662-01TB

Dimensions

LB	PP
TB	PPL
EB	PB
	R
	RL