

Features

1. Direct acting.
2. Quick response.
3. Timer for setting on/off time as optional accessory.
4. Good performance on resistance of counter flow.
5. Coil nut is available, please refer to page 5-3, 5-4.
6. CE conformity.



How to order

SPUY220	E	—	04	N	—	S1	L
Angle type Direct Acting	Diaphragm		Port size	Thread		Voltage	Led
	Blank : VITON E : EPDM H : HNBR		04 : 1/2"	Blank : G N : NPT R : Rc		S1 : 110VAC S2 : 220VAC S9 : 24VDC	Blank : W/O LED L : W/I LED

*Please contact our sales for normally open type.

How to order Repair kit

ZGSPUY	—	04	V
Repair kit	Port size	Diaphragm	
	04 : 1/2"	V : VITON E : EPDM H : HNBR	

Description	Qty.
T type plunger	1
O-ring	1

Specifications

Model	SPUY220-04
Port size	1/2"
Fluid	Standard: Compressed air Option: Hot water, Ammonia, Vacuum
Orifice	Ø9.5mm
Effective area	27.6mm ²
Acting	Direct acting
Seal	Standard: VITON, Option: EPDM
Operating pressure range	0 ~ 8 kgf/cm ²
Proof pressure	15 kgf/cm ²
Body material	SUS316
Fluid temperature	-10°C ~ 90°C
Ambient temperature	-10°C ~ 60°C
Installation	Any direction
Duty cycle	100% ED
Coil type	DIN
Protection class	IP65 (DIN 40 050)
Insulation class	F
Voltage tolerance	± 10%
Standard voltage	220VAC, 110VAC, 24VDC
Power consumption	AC110V: 25VA, AC220V: 27VA, 24VDC: 18.5W
Net weight	425g

Dimensions

