


Symbol



Features

- * Remove water and particle effectively.
- * 40 μ m and 5 μ m filter element are easily interchangeable and replaceable.
- * Accurate and easy pressure setting.
- * Lubricator oil can be replenished without stopping air supply.
- * Oil spray in mist ensures good lubrication for machines.



How to order

UAC30	-	02	N	C	H	A	SB
Filter Regulator+Lubricator		Port size	Thread	Filtration	Drain	Bowl	Spacer block
		02 1/4"	Blank G	Blank 5 μ m	Blank Semi-auto drain	Blank Standard bowl	
		03 3/8"	N NPT	C 40 μ m	H Manual drain	A Anti-acid & alkali bowl	
			R Rc		D Auto drain		

Specifications

Model	UAC30-02	UAC30-03
Port size	1/4"	3/8"
Fluid	Compressed air	
Regulator construction	Diaphragm	
Body material	Aluminum die-cast	
Bowl material	Polycarbonate	
Filtration	5 μ m (Standard), 40 μ m (Option)	
Operating pressure range	0.5 ~ 9.9 kgf/cm ²	
Proof pressure (Standard bowl)	15 kgf/cm ²	
Max. flow rate 6 kgf/cm ² (ANR)	1750 l/min	
Ambient temperature	-10 $^{\circ}$ C ~ 60 $^{\circ}$ C	
Lubricator oil (Recommended)	ISO-VG32	
Filter bowl capacity	20cc	
Lubricator bowl capacity	60cc	
Standard drain	Semi-auto drain (Drains below 0.5kgf/cm ²)	
Net weight	700g	
Accessories	Pressure gauge, Mounting bracket, Plug	

Dimensions

UAC30-02, 03

