


Symbol



Filter

Features

- * For high pressure use, corrosion and chemical resistance.
- * Good performance in chemically working environments and outdoor facility.
- * Suitable for semi-conductor industry.
- * The product effectively removes water and particle.
- * Strict quality control.



CE

How to order

USF		B		—		06		N		C		H		W	
SUS316 Stainless steel		Pressure				Port size		Thread		Filtration		Drain		Bowl viewer	
USF	Filter	Blank	0.5 ~ 28 kgf/cm ²			06	3/4"	Blank	G	Blank	5 μm	Blank	Semi-auto drain	Blank	W/O viewer
		B	0.5 ~ 12 kgf/cm ²			08	1"	N	NPT	C	40μm	H	Manual drain		
								R	Rc			D	Auto drain		
														W	Viewer (see *Remark below)

*Remark: Only for USFB (0.5 ~ 12 kgf/cm²)

Specifications

Model	USF-06	USF-08
Port size	3/4"	1"
Fluid	Compressed air	
Body material	Stainless steel SUS316	
Bowl material	Stainless steel SUS316	
Filter element material	Stainless steel SUS316	
Filtration	5 μm (Standard), 40 μm (Option)	
Operating pressure range	USFB: 0.5 ~ 12 kgf/cm ² USF: 0.5 ~ 28 kgf/cm ²	
Proof pressure	60 kgf/cm ² (Bowl viewer: 15 kgf/cm ²)	
Max. flow rate l/min (ANR)	B9600/19200	
Ambient temperature	-10℃ ~ 70℃	
Filter bowl capacity	110cc	
Standard drain	Manual drain	
Net weight	3950 g	
Accessories	Mounting bracket, Screw x 2	

Dimensions

USF-06,08

