


Symbol



Features

- * For high pressure use, corrosion and chemical resistance.
- * Good performance in chemically working environments and outdoor facility.
- * Lubricator oil can be replenished without stopping air supply.
- * Oil spray in mist ensures good lubrication for machines.



How to order

USL

SUS316 Stainless steel	
USL	Lubricator

B

Pressure	
Blank	0.5 ~ 28 kgf/cm ²
B	0.5 ~ 12 kgf/cm ²

06

Port size	
06	3/4"
08	1"

N

Thread	
Blank	G
N	NPT
R	Rc

W

Bowl viewer	
Blank	W/O viewer
W	Viewer (see *Remark below)

*Remark: Only for USLB (0.5 ~ 12 kgf/cm²)

Specifications

Model	USL-06	USL-08
Port size	3/4"	1"
Fluid	Compressed air	
Body material	Stainless steel SUS316	
Bowl material	Stainless steel SUS316	
Operating pressure range	USLB: 0.5 ~ 12 kgf/cm ² USL: 0.5 ~ 28 kgf/cm ²	
Proof pressure	60 kgf/cm ² (Bowl viewer: 15 kgf/cm ²)	
Max. flow rate l/min (ANR)	B13200/26400	
Ambient temperature	-10°C ~ 70°C	
Lubricator oil (Recommended)	ISO-VG32	
Lubricator bowl capacity	220cc	
Net weight	3360g	
Accessories	Mounting bracket, Screw x 2	

Dimensions

USL-06, 08

